

KX523

SNOW BLOWER



- Perfect For Snow And Site Cleanup
- Move Winter's Worst
- Hydraulic Chute Rotation
- Throws Snow Up To 40'

SNOW BLOWER

Model	KX523
Stock Code	39.55427
Auger	Double spiral serrated
Two Stage	Standard
Paddles	4
Chute	Rotates 220 degrees
Throwing Distance ¹	Approx 35-40 feet (10.6-12.2 meters)

Optional Accessories:

Chute Actuator	70.8025
12 Volt Switch/Plug (required for actuator)	70.4039
Deep Snow Auger Kit	70.8072

Dimensions:

Length	49 inches (124.5 cm)
Width	52 inches (132 cm)
Height	56.5 inches (144 cm)
Weight	467 pounds (212 kg)
Shipping Weight	625 pounds (283.5 kg)

¹ Dependent on wind and snow conditions

All specifications subject to change without notice or obligation

STANDARD FEATURES

- 2-Stage System
- Double spiral serrated auger
- Double hinged chute deflector with optional electric actuator
- Standard hydraulic controlled
- 220 degree rotation discharge chute
- Extra heavy-duty shaft and bearings
- Chute guard quick release rubber latches
- Chute liners to reduce snow leakage
- Front crossbar protection bumper
- Cleanup stick for dislodging clogged snow
- Ventrac Mount System

Optional Accessories

- 12 Volt Chute Actuator (requires 12 Volt Switch/Plug Kit)
- Deep Snow Auger Kit



3/8 inch thick abrasive resistant steel adjustable side skid shoes



One piece, shaft mounted adjustable cast iron skid shoe discs

The 52" wide Ventrac KX523 Snow Blower is built for commercial snow clearing operations of sidewalks, driveways, and other areas.

A two stage snow blower, the KX523 features a 16-inch diameter solid auger for best snow transfer, a large 20-inch diameter fan, and the ability to move 4500 pounds of snow per minute at distances up to 40 feet.

Standard features include adjustable cast iron skid shoe discs at the rear, high carbon hardened steel shoes at the side, and a reversible high carbon hardened steel cutting edge.

The hydraulically activated discharge chute can rotate 220 degrees, all from the convenience of Ventrac's exclusive S.D.L.A. Control System. Chute deflection is manually adjustable. An electric chute deflection controller is optional.

TRACTOR COMPATIBILITY KEY:

