



4200 Specification Comparison

4200

Gas Models, Liquid Cooled

Model	4227	4231
Stock Code	39.51200	39.51203
Trademark Name	Ventrac	Ventrac
Power Unit:		
Engine Manufacturer	Kawasaki Gas	B&S Vanguard Gas
Engine Model	FD750D	DM950G
Horsepower	27	31
Configuration	2-cylinder	3-cylinder
Cooling	Liquid-cooled	Liquid-cooled
CARB Compliant Engine	Yes	Yes
EPA Compliant Engine	Yes	Yes
Spin-on Oil Filter	Yes	Yes
Electrical System	20 amp	40 amp
Starter	Electric	Electric
Battery Capacity	12V/450CCA	12V/450CCA
Transmission:		
Drive	AWD	AWD
High/Low Shift from Seat	Std	Std
Transmission	Hydrostatic	Hydrostatic
Forward/Reverse Speed, High Range	0-10 MPH (0-16.1 KPH) Infinitely variable	0-10 MPH (0-16.1 KPH) Infinitely variable
Forward/Reverse Speed, Low Range	0-5.2 MPH (0-8.4 KPH) Infinitely Variable	0-5.2 MPH (0-8.4 KPH) Infinitely variable
Brakes	Hydro-Dynamic	Hydro-Dynamic
Spin-on Oil Filter-suction	25 microns	25 microns
Spin-on Oil Filter-pressure	10 microns	10 microns
Controls/Instrumentation:		
Steering	Power	Power
Blade Engage/PTO	Electric w/Brake	Electric w/Brake
Throttle Control/Choke	Std w/Manual Choke	Std w/Manual Choke
Operator Control *	S.D.L.A. / Std *	S.D.L.A. / Std *
Speed Control	Easy Shift	Easy Shift
Gauges:Temp/Hour/Tach	Std	Std
Park Brake/Emergency	16 in ² brake surface (103 cm ²)	16 in ² brake surface (103 cm ²)

Model	4227	4231
Other Features:		
Center Articulated Tractor	Yes	Yes
Turning Radius (appx)	43 inches	43 inches
Drive Tires	22 x 12-8 HD FieldTrax	22 x 12-8 HD FieldTrax
Optional Tires	21 x 11-8 Bar	21 x 11-8 Bar
	22 x 11-10 Turf Master	22 x 11-10 Turf Master
Seat-Spring Ride	Std	Std
Front Fenders	Std	Std
Headlights, Halogen	Std	Std
Fuel Tank Capacity	7.25 gal.	7.25 gal.
Visual Fuel Gauge Slot	Std	Std
Counter Weights (168 Lbs/76.2 kgs)	Std	Std
Weight Transfer System	Adjustable	Adjustable
Racor Fuel Water Separator	Opt	Opt
Foot Rest	Std	Std
Ventrac Mount System	Std	Std
ROPS Roll Bar	Std	Std
Weight (appx)	1460	1560

* S.D.L.A.- Speed, Direction, Lift, AUX. Control / single hand operation
Specifications Subject to Change Without Notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com



4200 Specification Comparison 4200

Diesel Models

Model	4226	4231TD
Stock Code	39.51204	39.51205
Trademark Name	Ventrac	Ventrac
Power Unit:		
Engine Model	DM950D	DM950DT
Horsepower	26.5	31
Configuration	3-cylinder	3-cylinder
Cooling	Liquid-cooled	Liquid-cooled
CARB Compliant Engine	Yes	Yes
EPA Compliant Engine	Yes	Yes
Spin-on Oil Filter	Yes	Yes
Electrical System	40 amp	40 amp
Starter	Electric	Electric
Battery Capacity	12V/450CCA	12V/450CCA
Transmission:		
Drive	AWD	AWD
High/Low Shift from Seat	Std	Std
Transmission	Hydrostatic	Hydrostatic
Forward/Reverse Speed, High Range	0-10 MPH (0-16.1 KPH) Infinitely variable	0-10 MPH (0-16.1 KPH) Infinitely variable
Forward/Reverse Speed, Low Range	0-5.2 MPH (0-8.4 KPH) Infinitely Variable	0-5.2 MPH (0-8.4 KPH) Infinitely variable
Brakes	Hydro-Dynamic	Hydro-Dynamic
Spin-on Oil Filter-suction	25 microns	25 microns
Spin-on Oil Filter-pressure	10 microns	10 microns
Controls/Instrumentation:		
Steering	Power	Power
Blade Engage/PTO	Electric w/Brake	Electric w/Brake
Throttle Control/Choke	Std w/Glow Plug	Std w/ Glow Plug
Operator Control *	S.D.L.A. / Std *	S.D.L.A. / Std *
Speed Control	Easy Shift	Easy Shift
Gauges: Temp/Hour/Tach	Std	Std
Park Brake/Emergency	16 in ² brake surface (103 cm ²)	16 in ² brake surface (103 cm ²)

Model	4226	4231TD
Other Features:		
Center Articulated Tractor	Yes	Yes
Turning Radius	43"	43"
Drive Tires	22 x 12-8 HD Field Trax	22 x 12-8 HD Field Trax
Optional Tires	21 x 11-8 Bar 22 x 11-10 Turf Master	21 x 11-8 Bar 22 x 11-10 Turf Master
Seat-Spring Ride	Std	Std
Front Fenders	Std	Std
Headlights, Halogen	Std	Std
Fuel Tank Capacity	7.25 gal.	7.25 gal.
Visual Fuel Gauge Slot	Std	Std
Counter Weights	180 lbs.	180 lbs.
Weight Transfer System	Adjustable	Adjustable
Racor Fuel Water Separator	Std	Std
Foot Rest	Std	Std
Ventrac Mount System	Std	Std
ROPS	Std / Fold Down Opt.	Std / Fold Down Opt.
Weight (appx)	1560	1580

* S.D.L.A.- Speed, Direction, Lift, AUX. Control / single hand operation
Specifications Subject to Change Without Notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com