

The versatile Ventrac Spreader ES220 is designed and built to spread Seed, Fertilizer and Penn Mulch. The spreader is capable of being rear* or front mounted**. An electronic control box comes standard and features an electronic speed control and On/Off switch

The mounting hitch is a standard 2 inch receiver which means this spreader not only will work on Ventrac tractors but also can be fitted to any vehicle with a 2 inch receiving hitch.

* Rear mounting available on 4000 series only

** Front mounting requires 2-N-1 adapter.
Rear weights are recommended.



Standard Features:

- 220 Pound (100 kg) Capacity
- Spreads a Variety of Material - Seed, Fertilizer & Penn Mulch
- Mounts Rear or Front
- 2 inch receiver hitch
- Hopper Cover
- Electronic Control Box (Speed Control – On/Off Switch)
- Remote Gate & Diffuser Control
- Spread 3 to 25 ft. (.9-7.6 meters)

Requires 12 Volt Kit



Specifications

Accessories

Spreader ES220



Spreader ES220

Stock Code	39.55500
12 Volt Power Outlet, Rear (required for rear mount, 4000 series)	70.4087
12 Volt Switch and Plug * (required for front mount**, 4000 series)	70.4039
**2-N-1 Receiver Tube required for mounting to Front	70.2001
12 Volt Switch and Plug** (required for LE3100 & LT3200 tractors)	70.3016
**2-N-1 Receiver Tube required for mounting to Front	70.2001
Material Bin Construction	Polymer
Spreader RPMs	80-750 RPMs
Motor Current	20 amps
Material Spread	3-25 feet (.9-7.6 meters)

Optional Accessories

Hitch Kit for rear weight bar	70.8028
-------------------------------	---------

Dimensions

Length	38.5 inches (98 cm)
Width	34 inches (86 cm)
Height	44 inches (112 cm)
Weight	90 lbs (41 kg)
Shipping Weight	155 lbs (70.3 kg)
Shipping Dimensions (LxWxH)	39x32x38 inches (99x81x97 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com