Accessories
ES220 Spreader

SPECIFICATIONS

Stock Code	39.55500
Material Bin Construction	Polymer
Spreader RPMs	80-750 RPMs
Motor Current	20 amps
Material Spread	6 feet (1.6 meters)
Mounting Options	
Rear Mount, 4500 Tractor	
12 Volt Power Rear Outlet	70.4105
Front Mount, 4500 Tractor	
12 Volt Front Switch & Plug	70.4104
2-N-1 Receiver Tube	70.2001
Front Mount, 3400 Tractor	
12 Volt Front Switch & Plug	70.3036
2-N-1 Receiver Tube	70.2001
Dimensions	
Length	38.5 inches (98 cm)
Width	34 inches (86 cm)
Height	44 inches (112 cm)
Weight	90 lbs (41 kg)

All specifications subject to change without notice or obligation

The versatile Ventrac Spreader ES220 is designed and built to spread Seed, Fertilizer and Penn Mulch. The spreader is capable of being rear or front mounted. An electronic control box comes standard and features an electronic speed control and On/Off switch

The mounting hitch is a standard 2 inch receiver which means this spreader not only will work on Ventrac tractors but also can be fitted to any vehicle with a 2 inch receiving hitch.

STANDARD FEATURES

- 220 Pound (100 kg) Capacity
- Spreads a Variety of Material:
  Seed, Fertilizer and Penn Mulch
- Mounts Rear or Front
- 2 inch receiver hitch
- Hopper Cover
- Electronic Control Box
  (Speed Control – On/Off Switch)
- Remote Gate & Diffuser Control
- Spread 6 feet (1.6 meters)

Requires 12 Volt Kit (See Mounting Options)

Note: The ES220 is not intended for salt or de-icing materials. For de-icing materials, use the Ventrac SA250 drop spreader

TRACTOR COMPATIBILITY KEY: 3400 4500

500 Venture Drive
Orrville, OH 44667
1.866.836.8722
Fax: 330.683.0000
www.ventrac.com
info@ventrac.com